

Huawei

H11-828

Huawei Certified Network Professional“ Unified Communication (HCNP-UC)

**For More Information – Visit link below:
<https://www.certsgrade.com/>**

Version = Product



Question: 1

eSpace Desktop needs to register with several devices during a login. What are the devices? (Multiple Choice)

- A. eServer
- B. BMU
- C. IPPBX
- D. Console server

Answer: A C

Question: 2

Which of the following statements is INCORRECT as regard to the CDR system?

- A. The unified gateway provides an open and secure interface for a third-party billing system or center to obtain CDRs.
- B. BMU provides the CDR query function.
- C. Original CDRs are stored in the CDR pool of the unified gateway.
- D. After CDRs are obtained from the CDRServer, the CDRs in the current folder are deleted and saved to the backup folder.

Answer: A

Question: 3

After a user logs in to a mobile client and makes a VoIP call, a message indicating VoIP registration failure is displayed. Which of the following are possible causes? (Multiple Choice)

- A. The area policy is incorrectly configured on the BMU.
- B. The SBC that supports NAT traversal through the media proxy function has both internal and external network IP addresses, but network routing of the external network is not configured.
- C. The MAA service is faulty.
- D. The connection between the MAA and the U1900 is abnormal.

Answer: A B

Question: 4

About a multi-node centralized network, which of the following statements are CORRECT? (Multiple Choice)

- A. All users have their services configured and controlled in a unified manner on the central node.
- B. In normal conditions, the local node does not accept registration requests from SIP users.
- C. POTS users on the local node register with the central node directly.
- D. On the central node, you can view the license information about the local node.

Answer: A B

Question: 5

In the eSpace Audio Recorder solution, HWLogIMP works in () mode.

- A. C/S
- B. B/S
- C. A/S
- D. A/A

Answer: A

Question: 6

In a multi-node centralized network, the status of SIP users of the local node is normally displayed as () on the local node.

- A. idle
- B. fault
- C. busy

Answer: B

Question: 7

During the switchover between the active node and the standby node in the remote disaster recovery scenario, ongoing voice conferences will be interrupted.

- A. TRUE
- B. FALSE

Answer: A

Question: 8

eSpace Desktop A and eSpace Mobile B register with the same eServer and are both online. If A transfers a file to B, the path along which the file is transferred is ().

- A. A->B
- B. A->eServer->B
- C. A->eServer->MAA->B
- D. A->MAA->eServer->MAA->B
- E. A->MAA->eServer->B

Answer: A

Question: 9

A company's branch has 20 IP phones that need to register with the primary node. Which of the following devices is most cost-effective and supports local regeneration for the branch?

- A. IAD132E(T)
- B. U1911
- C. U1981
- D. U1960

Answer: B

Question: 10

An AR provides multiple statistics query commands. SIP message statistics can be queried in all views,

- A. TRUE
- B. FALSE

Answer: B

For More Information – **Visit link below:**
<https://www.certsgrade.com/>

PRODUCT FEATURES

-  **100% Money Back Guarantee**
-  **90 Days Free updates**
-  **Special Discounts on Bulk Orders**
-  **Guaranteed Success**
-  **50,000 Satisfied Customers**
-  **100% Secure Shopping**
-  **Privacy Policy**
-  **Refund Policy**

20% Discount Coupon Code: 20off2018

