

Huawei

H35-561
HCNP - LTE RNP & RNO

Questions And Answers PDF Format:

For More Information – Visit link below:

<https://www.certsgrade.com/>

Version = Product



Latest Version: 6.0

Question: 1

Which of the following events can be used to trigger inter-frequency switching? (multiple choice)

- A. A2
- B. A3
- C. A4
- D. A5

Answer: B, C, D

Question: 2

How many types of TDD uplink and downlink subframe configurations are there?

- A. 3
- B. 5
- C. 7
- D. 9

Answer: C

Question: 3

When X2 handover cannot be performed between eNodeBs, S1 handover is performed.

- A. True
- B. False

Answer: A

Question: 4

How many configurations are there for R8 TDD special subframe configuration?

- A. 3

-
- B. 5
 - C. 7
 - D. 9

Answer: D

Question: 5

In which of the following messages will the tracking area information be sent to the MME for consistency check?

- A. S1AP: E-RAB setup request
- B. RRC: RRC connection request
- C. S1AP: Initil context setup request
- D. S1AP: S1 setup request

Answer: D

For More Information – **Visit link below:**
<http://www.certsgrade.com/>

PRODUCT FEATURES

-  **100% Money Back Guarantee**
-  **90 Days Free updates**
-  **Special Discounts on Bulk Orders**
-  **Guaranteed Success**
-  **50,000 Satisfied Customers**
-  **100% Secure Shopping**
-  **Privacy Policy**
-  **Refund Policy**

Discount Coupon Code: **CERTSGRADE10**

