

## *SAS Institute*

*A00-402*

*SAS Viya 3.5 Supervised Machine Learning Pipelines*

**Questions And Answers PDF Format:**

**For More Information – Visit link below:**

**<https://www.certsgrade.com/>**

*Version = Product*



---

# Latest Version: 6.0

## Question: 1

For a new project that you are creating in SAS Model Studio, you wish to use a SAS data set that is not in memory but exists on your connected server (not the local machine). In which tab would this data set be located?

Response:

- A. Data Sources
- B. Available
- C. Import
- D. Load Data

**Answer: A**

## Question: 2

Which feature extraction method can take both interval variables and class variables as inputs?

Response:

- A. Principal component analysis
- B. Autoencoder
- C. Singular value decomposition
- D. Robust PCA

**Answer: B**

## Question: 3

A project has been created and a pipeline has been run in Model Studio. Which project setting can you edit?

Response:

- A. Advisor Options for missing values
- B. Rules for model comparison statistic
- C. Partition Data percentages
- D. Event-based Sampling proportions

**Answer: B**

### Question: 4

Which statement is true regarding decision trees and models based on ensembles of trees?

Response:

- A. In the gradient boosting algorithm, for all but the first iteration, the target is the residual from the previous decision tree model.
- B. For a Forest model, the out-of-bag sample is simply the original validation data set from when the raw data partitioning took place.
- C. In the Forest algorithm, each individual tree is pruned based on using minimum Average Squared Error.
- D. A single decision tree will always be outperformed by a model based on an ensemble of trees.

**Answer: A**

### Question: 5

What is another term for a feature in predictive modeling?

Response:

- A. Instance
- B. Input
- C. Target
- D. Outcome

**Answer: B**

### Question: 6

When you scale the input variables for a binary target using support vector machines, what happens to the inputs?

Response:

- A. Values are scaled to range from -1 to 1.
- B. Values are scaled to range from 0 to 1.
- C. Values are scaled to range from negative infinity to infinity.
- D. Values are scaled to be positive.

**Answer: B**

### Question: 7

What is the purpose of the Bonferroni correction during a decision tree split search?

Response:

- A. To adjust for the number of irrelevant inputs.
- B. To prevent overfitting due to the number of tests needed to test each split point.
- C. To correct for the number of correlated inputs and allow for surrogate rules.
- D. To maintain overall confidence by inflating the p-values.

**Answer: D**

### Question: 8

The input variables have missing values. What should you do before running a Decision Tree node with these input variables?

Response:

- A. impute all missing values using the Impute node
- B. impute only interval variables using the Impute node but do not impute the class variables
- C. impute only class variables using the Impute node but do not impute the interval variables
- D. not impute any missing values because trees can handle them

**Answer: D**

### Question: 9

As the number of input variables in a problem increases, there is an exponential increase in the number of observations needed to densely populate the feature space. This is referred to as:

Response:

- A. Problem of rare events
- B. Multicollinearity
- C. Curse of Dimensionality
- D. Underfitting

**Answer: C**

---

For More Information – **Visit link below:**  
**<http://www.certsgrade.com/>**

## PRODUCT FEATURES

-  **100% Money Back Guarantee**
-  **90 Days Free updates**
-  **Special Discounts on Bulk Orders**
-  **Guaranteed Success**
-  **50,000 Satisfied Customers**
-  **100% Secure Shopping**
-  **Privacy Policy**
-  **Refund Policy**

Discount Coupon Code: **CERTSGRADE10**

