

## *Dell EMC*

*D-PVM-DS-23*

*Dell Technologies PowerMax and VMAX Family Solutions Design 2023*

**Questions And Answers PDF Format:**

**For More Information – Visit link below:**

**<https://www.certsgrade.com/>**

*Version = Product*



---

# Latest Version: 6.0

## Question: 1

A storage architect is designing a PowerMax solution. The architect must customize the maximum SRDF/A cache usage. Which system view can the architect use to meet this requirement?

Response:

- A. Performance
- B. System Properties
- C. Data Protection
- D. System Settings

**Answer: D**

## Question: 2

A customer has Open Systems, Mainframe, and IBM i systems in the data center. Which arrays can be used to consolidate these independent systems into a single array?

Response:

- A. VMAX All Flash 950 and PowerMax 2000
- B. PowerMax 8000 and VMAX All Flash 950
- C. PowerMax 2000 and PowerMax 8000
- D. VMAX All Flash 250 and VMAX All Flash 950

**Answer: B**

## Question: 3

In what format can loaded and mapped BCSD performance data be exported?

Response:

- A. DOC
- B. XML
- C. CSV
- D. PFD

**Answer: C**

### Question: 4

What types of files are supported for import into Sizer?

Response:

- A. TTP, DCF, CSV, and configuration files
- B. TTP, CSV, and configuration files only
- C. BTP, DCF, CSV, and configuration files
- D. BTP, DCF, and configuration files only

**Answer: C**

### Question: 5

When adding device pairs to an SRDF/Metro configuration using the -exempt option, what prevents a device pair from being added?

Response:

- A. R2 device is larger than the R1 device
- B. Source group and device pair are in SRDF/S mode
- C. R1 device is the source of a TimeFinder data copy
- D. Source group and device pair are in SRDF/Adaptive Copy mode

**Answer: A**

### Question: 6

Open Replicator is being used to copy data from a VNX to a PowerMax. During the migration, users experience latency when accessing the storage from the VNX. What can be done to address the issue?

Response:

- A. Reduce Pace and Ceiling Value
- B. Set Pace to 0 and Ceiling to 50%
- C. Reduce Ceiling Value
- D. Nothing, because copying has started

**Answer: C**

### Question: 7

---

What is the default HTTPS port assignment for communication of VSI/IAPI requests sent to REST API of Unisphere for PowerMax?

Response:

- A. 5441
- B. 5443
- C. 8441
- D. 8443

**Answer: D**

### Question: 8

Which role is required to rename a service level in Unisphere for PowerMax?

Response:

- A. Administrator
- B. Storage Administrator
- C. Security Administrator
- D. VM Administrator

**Answer: B**

### Question: 9

While designing a SnapVX solution for a volume that is mapped to a Unix server, a storage architect decides to take three snapshots per day and retain them for six weeks. The Unix team would like to take a few on-demand snapshots before and during an upgrade activity.

How many snapshots can be taken without disrupting the daily snapshots?

Response:

- A. 130
- B. 256
- C. 898
- D. 1024

**Answer: A**

### Question: 10

By what percentage is SRDF throughput improved by SiRT?

Response:









- 
- A. 10%
  - B. 20%
  - C. 30%
  - D. 40%

<b>Answer: B</b>
------------------

---

For More Information – **Visit link below:**  
**<https://www.certsgrade.com/>**

## PRODUCT FEATURES

-  **100% Money Back Guarantee**
-  **90 Days Free updates**
-  **Special Discounts on Bulk Orders**
-  **Guaranteed Success**
-  **50,000 Satisfied Customers**
-  **100% Secure Shopping**
-  **Privacy Policy**
-  **Refund Policy**

**16 USD Discount Coupon Code: **NB4XKTMZ****

